NSN 5905-01-229-3908

Film Fixed Resistor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5905-01-229-3908 |
|----------------------------------------------------------------------------------------------------------------------------------------------|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
| -100.0 to 100.0 |
| Electrical Resistance: |
| 4.700 kilohms |
| Resistance Tolerance In Percent: |
| -2.000 to 2.000 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 70.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 150.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0 to 150.0 |
| Inclosure Method: |
| Encapsulated |
| Terminal Type: |
| Wire lead |
| Mil-std-1276 Wire Lead Type Designator: |
| C |
| Reliability Indicator: |
| Established |
| Reliability Failure Rate Level In Percent: |
| 0.001 |
| Terminal Length: |
| 1.500 inches |
| Body Diameter: |
| 0.190 inches |
| Body Length: |
| 0.562 inches |
| Power Dissipation Rating In Watts: |
| 1.000 free air |
| End Application: |
| Pump ctfgl |
| Unpackaged Unit Weight: |
| 1.5 grams |
| Style Designator: |
| Axial terminal each end |
| Test Data Document: |
| 81349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81349-mil-r-39017/3 government specification |

N/a

Shelf Life:

NSN 5905-01-229-3908

Film Fixed Resistor - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

No

Fiig:

A001a0