NSN 5905-01-229-8605

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-229-8605

view Offilite at https://aerobasegroup.com/hist//0300-01-223-0000
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-20.0/+20.0
Electrical Resistance:
20.000 kilohms
Resistance Tolerance In Percent:
-1.000/+1.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
275.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+275.0
Inclosure Method:
Encapsulated
Terminal Type:
Wire lead
Mil-std-1276 Wire Lead Type Designator:
C
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.001
Terminal Length:
1.500 inches
Body Diameter:
0.375 inches
Body Length:
1.780 inches
Power Dissipation Rating In Watts:
10.000 free air
End Application:
An/sps-6 (v) 9
Cubic Measure (non-core):
0.197 cubic inches
Unpackaged Unit Weight:
13.0 grams
Style Designator:
Axial terminal each end
Test Data Document:
81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-r-39007/7 government specification

NSN 5905-01-229-8605

Inductive Wire Wound Fixed Resistor - Page 2 of 2



S	he	Ιf	Life:
•		••	Liic.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0