Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-229-8636

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.719 inches

First Flat Length:

0.344 inches

Flat Height:

0.216 inches

Body Diameter:

1.094 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.000 inches

Mounting Bushing Length:

0.500 inches

Body Length:

1.187 inches

Overall Diameter:

1.750 inches

Shaft Style:

Round, flatted

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

270.0

Maximum Starting Torque:

6.00 inch-ounces

Maximum Running Torque:

6.00 inch-ounces

Maximum Stop Torque:

192.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.531 inches



End Application	:
An/gsq-t14	
Screw Thread D	iameter:
0.375 inches	
Screw Thread S	eries Designator:
Unef	
Screw Thready	Qty Per Inch (tpi):
32.0	
Terminal Locati	on:
Radially position	ed over less than half the circumference
Mounting Metho	d:
Standard bushing	
Electrical Resist	ance Per Section:
600.000 ohms al	sections
Rotary Actuator	Travel In Angular Deg:
312.0	
Ambient Tempu	rature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 all sections	
Power Dissipati	on Rating Per Section In Watts:
2.0 free air all se	ctions
Resistance Tole	rance Per Section In Percent:
-10.0/+10.0 all se	ctions
Actuator Travel	Control Feature:
Stops	
Ambient Tempu	rature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections	
Standard Taper	Curve Per Section:
A all sections	
Test Data Docu	nent:
11293-37-13463	57 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes ar	ny specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type A	and Quantity:
3 tab, solder lug	
Shelf Life:	
N/a	
Unit Of Measure	
Demilitarization	
No	
Fiig:	
A002a0	