NSN 5905-01-229-9286

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-229-9286

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-260.0/+260.0
Electrical Resistance:
33.000 ohms
Resistance Tolerance In Percent:
-5.000/+5.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
350.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+350.0
Inclosure Method:
Encapsulated
Terminal Type:
Tab, solder lug
Reliability Indicator:
Not established
Terminal Length:
0.563 inches
Body Diameter:
1.312 inches
Body Length:
10.500 inches
Power Dissipation Rating In Watts:
210.000 free air
Terminal Width:
0.328 inches
End Application:
An/bps14to15e
Cubic Measure (non-core):
14.195 cubic inches
Unpackaged Unit Weight:
0.62 grams
Style Designator:
Radial terminal each end
Test Data Document:
81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-26/3 government specification

N/a

Shelf Life:

NSN 5905-01-229-9286

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A001a0