NSN 5905-01-230-0551

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-230-0551 **Section Quantity: Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Terminal Length:** 0.172 inches **Mounting Hole Diameter:** 0.078 inches **Shaft Diameter:** 0.075 inches **Shaft Length:** 0.045 inches **Body Length:** 0.538 inches **Body Width:** Between 0.203 inches and 0.235 inches **Body Height:** Between 0.484 inches and 0.516 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Running Torque:** 5.00 inch-ounces **Center To Center Distance Between Terminals:** Between 0.190 inches and 0.210 inches **Lateral Distance Between Mounting Hole Centers:** 0.520 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Lower adjacent side single row **Mounting Method:** Unthreaded hole **Cubic Measure:** 0.065 cubic inches

Electrical Resistance Per Section: 5.0 kilohms single section

NSN 5905-01-230-0551

No Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Center To Center Distance Between Center Terminal And Outside Terminal: Between 0.090 inches and 0.110 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Power Dissipation Rating Per Section In Watts:** 0.75 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section **Special Features:** Terminals are hot solder dipped after final assembly **Precious Material And Location:** Terminals gold **Precious Material: Terminal Type And Quantity:** 3 pin Shelf Life: N/a **Unit Of Measure:** Demilitarization: