## NSN 5905-01-230-2851

Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-230-2851

Tempurature Coefficient Of Resistance In Dam Box Coloius					
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:					
-30.0/+30.0					
Electrical Resistance:					
133.000 ohms					
Resistance Tolerance In Percent:					
-1.000/+1.000					
Ambient Tempurature In Deg Celsius At Full Rated Power:					
25.0					
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:					
275.0					
Tempurature Range Of Tempurature Coefficient In Deg Celsius:					
-55.0/+275.0					
Inclosure Method:					
Encased					
Terminal Type:					
Tab, solder lug					
Reactance Characteristic:					
Noninductive					
Reliability Indicator:					
Established					
Reliability Failure Rate Level In Percent:					
0.010					
Terminal Length:					
0.266 inches					
Body Length:					
0.600 inches					
Body Width:					
0.334 inches					
Body Height:					
0.320 inches					
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:					
0.444 inches					
Power Dissipation Rating In Watts:					
3.000 free air					
End Application:					
4920-01-179-8469					
Mounting Hole Size:					
0.093 inches					
Style Designator:					
Axial terminal (s)					
Test Data Document:					

81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5905-01-230-2851

Wire Wound Fixed Resistor - Page 2 of 2



S	pe	cifi	cat	ion	Data:

81349-mil-r-39009/2 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A001a0