## NSN 5905-01-230-6470

Film Fixed Resistor - Page 1 of 2

No



View Online at https://aerobasegroup.com/nsn/5905-01-230-6470

Tompurature Coefficient Of Posistance In Pom Per Dog Coloius
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -50.0/+50.0
Electrical Resistance:
6.490 megohms  Resistance Tolerance In Percent:
-0.100/+0.100
Ambient Tempurature In Deg Celsius At Full Rated Power:
125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
175.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+175.0
Inclosure Method:
Hermetically sealed  Torminal Types
Terminal Type: Wire lead
Reliability Indicator:  Established
Reliability Failure Rate Level In Percent:
0.001
Terminal Length: 1.500 inches
Body Diameter: 0.250 inches
Body Length:
0.750 inches  Power Discination Pating In Wetter
Power Dissipation Rating In Watts:
0.500 free air
End Application:
Mgcs/meca t s
Style Designator:
Axial terminal each end Test Pate Resuments
Test Data Document:
81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-55182/6 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

## NSN 5905-01-230-6470

Film Fixed Resistor - Page 2 of 2



Fiig:

A001a0