NSN 5905-01-230-6489

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-230-6489 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.156 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.813 inches **Mounting Bushing Length:** 0.406 inches **Body Length:** 0.625 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 292.0 **Maximum Starting Torque:** 12.00 inch-ounces **Maximum Running Torque:** 12.00 inch-ounces **Maximum Stop Torque:** 192.00 inch-ounces **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Mechanical Backlash In Deg Angular Rotation:** 1.5 **Fragility Factor:** Moderately rugged **End Application:**

An/tlq-17 (v)

Screw Thread Diameter:

0.375 inches

NSN 5905-01-230-6489 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thread Series Designator:
Jnef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Features Provided:
Panel seal and shaft seal
Electrical Resistance Per Section:
5.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
312.0
Resistance Tempurature Characteristic Range Per Section In Percent:
+0.0 to 6.9 -55 degrees celsius single section and +0.0 to 3.8 -25 degrees celsius single section and +0.0 to 1.9 0 degrees celsius single
section and -2.5 to 2.5 85 degrees celsius single section and +0.0 to 5.6 120 degrees celsius single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
1.125 free air single section
Resistance Tolerance Per Section In Percent:
10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
M single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No No
Filg:
A002a0