

View Online at https://aerobasegroup.com/nsn/5905-01-230-9639

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Overall Length:**

2.125 inches

#### **Body Diameter:**

0.890 centimeters

#### Shaft Diameter:

0.125 inches

#### Shaft Length:

0.625 inches

#### Mounting Bushing Length:

## 0.313 inches

**Body Length:** 

1.500 inches

#### **Overall Diameter:**

1.250 inches

# Shaft Style:

Round, slotted

## Shaft Bearing Type:

Sleeve

#### Actuator Type:

Single shaft

#### Effective Electrical Rotation In Deg Angular Rotation:

3600.0

#### Maximum Starting Torque:

0.70 inch-ounces

#### Maximum Running Torque:

0.60 inch-ounces

#### Maximum Stop Torque:

48.00 inch-ounces

#### **Nonturn Device Location:**

At 12 oclock

## Nonturn Device Radius:

0.302 inches

### Shaft End Play:

0.005 inches

## Shaft Runout:

0.002 inches



Lateral Runout: 0.002 inches **Pilot Diameter Runout:** 0.001 inches Shaft Radial Play: 0.002 inches Mechanical Backlash In Deg Angular Rotation: 1.0 **End Application:** Lgm-30f/gmiss Screw Thread Diameter: 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 200.0 ohms c and better flooring **Rotary Actuator Travel In Angular Deg:** 3600.0 **Function Conformity Tolerance Per Section:** -0.25/+0.25 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section **Power Dissipation Rating Per Section In Watts:** 2.0 7th secondary quality **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -3.0/+3.0 single section **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:** 7 oclock all primaries Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Test Data Document:** 

81349-mil-r-12934 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

# NSN 5905-01-230-9639

Precision Wire Wound Variable Resistor - Page 3 of 3



# Terminal Type And Quantity:

3 turret

## Specification Data:

81349-mil-r-12934/31 government specification

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A002a0