NSN 5905-01-230-9641

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-230-9641

Section Quantity:
Body Style:
Rectangular
Reliability Indicator:
Not established
Body Length:
0.750 inches
Body Width:
0.250 inches
Body Height:
0.165 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
7200.0
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
Fragility Factor:
Moderately delicate
Terminal Location:
Dual inline
Mounting Method:
Terminal
Features Provided:
Hermetically sealed
Electrical Resistance Per Section:
2.000 megohms single section
Rotary Actuator Travel In Angular Deg:
7200.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0 to 100.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Clutch

NSN 5905-01-230-9641

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2

Per Section At Full Rated Power:



Ambient Tempurature In Deg Celsius
70.0 single section
Precious Material And Location:
Terminal surfaces gold
Precious Material:
Gold
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A002a0