Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-230-9642

# Section Quantity:

1

Body Style:

Rectangular

## **Reliability Indicator:**

Not established

### Body Length:

0.750 inches

#### **Body Width:**

0.250 inches

**Body Height:** 

0.165 inches

Actuator Type:

#### Flush drive with slot-hole

### Effective Electrical Rotation In Deg Angular Rotation:

7200.0

### Maximum Starting Torque:

5.00 inch-ounces

#### Maximum Running Torque:

5.00 inch-ounces

### Fragility Factor:

Moderately delicate

# **Terminal Location:**

Dual inline

### Mounting Method:

Terminal

#### **Features Provided:**

Hermetically sealed

### **Electrical Resistance Per Section:**

200.000 ohms single section

### **Rotary Actuator Travel In Angular Deg:**

7200.0

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

### Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

# Power Dissipation Rating Per Section In Watts:

1.0 free air single section

## **Resistance Tolerance Per Section In Percent:**

-5.0 to 5.0 single section

### Actuator Travel Control Feature:

Clutch



## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

## Standard Taper Curve Per Section:

A single section

# **Precious Material And Location:**

Terminal surfaces gold

# **Precious Material:**

Gold

## Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A002a0