

View Online at <https://aerobasegroup.com/nsn/5905-01-231-1294>

**Temperature Coefficient Of Resistance In Ppm Per Deg Celsius:**

-50.0 to 50.0 first temp coefficient

**Electrical Resistance:**

100.000 kilohms each resistor

**Resistance Tolerance In Percent:**

-1.000 to 1.000 each resistor

**Ambient Temperature In Deg Celsius At Full Rated Power:**

70.0

**Ambient Temperature In Deg Celsius At Zero Percent Rated Power:**

125.0

**Temperature Range Of Temperature Coefficient In Deg Celsius:**

-55.0 to 125.0 temp range of first temp coefficient

**Inclosure Method:**

Hermetically sealed

**Terminal Quantity:**

16

**Terminal Type:**

Pin

**Mil-std-1276 Wire Lead Type Designator:**

K

**Reliability Indicator:**

Not established

**Terminal Length:**

0.250 inches

**Body Length:**

0.250 inches

**Body Width:**

0.390 inches

**Body Height:**

Between 0.050 inches and 0.070 inches

**Schematic Diagram Designator:**

Isolated array

**Power Dissipation Rating In Watts:**

0.125 total network

**Err Default:**

Between 0.016 inches and 0.018 inches

**End Application:**

F/1f-15a acrf

**Identical Value Resistor Quantity:**

8 each resistor

**Precious Material And Location:**

Bonding wire gold and terminal surfaces gold

**Style Designator:**

Flat pack

**Test Data Document:**

82577-955234 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A001a0