NSN 5905-01-231-2462

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-231-2462

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
Between 1.0295 inches and 1.0300 inches
Pilot Length:
0.0400 inches
Overall Length:
1.385 inches
Undercut Diameter:
1.000 inches
Undercut Width:
0.0600 inches
Body Diameter:
1.094 inches
Shaft Length:
0.750 inches
Body Length:
0.635 inches
Overall Diameter:
1.375 inches
Mounting Lip Diameter:
1.0940 inches
Mounting Lip Depth:
0.0600 inches
Shaft Style:
Round
Shaft Bearing Type:
Ball
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
360.0
Maximum Starting Torque:
0.40 inch-ounces
Maximum Running Torque:
0.40 inch-ounces
Shaft End Play:
0.005 inches

NSN 5905-01-231-2462

Precision Wire Wound Variable Resistor - Page 2 of 2



Shaft Runout:
0.001 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.001 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
5.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-1.00 to 1.00 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
Single section 360 degrees sine-cosine
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0 to 20.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:
_
Demilitarization:
No
Fiig:
A002a0