## NSN 5905-01-231-5146

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-231-5146

## **Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:**

-250.0 to 250.0 first temp coefficient

**Electrical Resistance:** 

784.000 ohms intermediate resistance value

**Resistance Tolerance In Percent:** 

-2.000 to 2.000 each resistor

Ambient Tempurature In Deg Celsius At Full Rated Power:

70.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

**Tempurature Range Of Tempurature Coefficient In Deg Celsius:** 

-55.0 to 125.0 temp range of first temp coefficient

**Inclosure Method:** 

Encapsulated

**Terminal Quantity:** 

16

**Terminal Type:** 

Tab, solder lug

**Reliability Indicator:** 

Not established

**Terminal Length:** 

Between 0.125 inches and 0.150 inches

**Body Length:** 

Between 0.784 inches and 0.876 inches

**Body Width:** 

Between 0.240 inches and 0.305 inches

**Body Height:** 

0.200 inches

**Schematic Diagram Designator:** 

Isolated array

**Power Dissipation Rating In Watts:** 

1.500 total network

Err Default:

Between 0.015 inches and 0.022 inches

**End Application:** 

F100-pw-220

**Identical Value Resistor Quantity:** 

4 lowest resistance value

**Unpackaged Unit Weight:** 

2.0 grams

**Style Designator:** 

**Dual inline** 

## NSN 5905-01-231-5146

Film Fixed Resistor Network - Page 2 of 2



## **Test Data Document:**

73030-5e4795/139 drawing (this	is the basic governing drawing,	such as a contractor drawing,	original equipment manufacturer	drawing,
etc.; excludes any specification,	standard or other document that	at may be referenced in a basic	governing drawing)	

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A001a0