NSN 5905-01-231-5147

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-231-5147 **Section Quantity:** 2 **Body Style:** Rectangular w/slide control **Reliability Indicator:** Not established **Overall Length:** 21.800 inches **Overall Height:** 5.600 inches **Overall Width:** 7.250 inches **Mounting Slot Width:** 0.250 inches **Body Length:** 21.800 inches **Body Width:** 7.250 inches **Body Height:** 5.600 inches **Actuator Type:** Slider **Longitudinal Actuator Travel:** 20.500 inches **Longitudinal Actuator Effective Electrical Stroke Length:** 20.500 inches **End Application:** An/tsc-99 **Mounting Facility Quantity: Terminal Location:** Front-rear **Mounting Method:** Slot **Cubic Measure:** 885.080 cubic inches **Electrical Resistance Per Section:** 70.0 ohms all sections Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

280.0 all sections

Power Dissipation Rating Per Section In Watts:

2000.0 free air all sections

NSN 5905-01-231-5147

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 all sections
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 all sections
Standard Taper Curve Per Section:
A all sections
Terminal Type And Quantity:
8 binding post
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No