

View Online at <https://aerobasegroup.com/nsn/5905-01-231-6540>

**Section Quantity:**

2

**Body Style:**

Rectangular bushing mounted

**Reliability Indicator:**

Not established

**Shaft Diameter:**

0.250 inches

**Body Length:**

1.250 inches

**Body Width:**

0.625 inches

**Body Height:**

0.625 inches

**Undercut Diameter:**

0.125 inches

**Shaft Style:**

Round, stepped

**Shaft Bearing Type:**

Sleeve

**Actuator Type:**

Dual concentric

**Effective Electrical Rotation In Deg Angular Rotation:**

240.0

**Maximum Starting Torque:**

2.00 inch-ounces

**Maximum Running Torque:**

2.00 inch-ounces

**Maximum Stop Torque:**

64.00 inch-ounces

**Nonturn Device Location:**

At 3 oclock

**Nonturn Device Radius:**

0.305 inches

**Screw Thread Diameter:**

0.375 inches

**Mounting Method:**

Standard bushing

**Rotary Actuator Travel In Angular Deg:**

300.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 all sections

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-150.0 to 150.0 all sections

**Power Dissipation Rating Per Section In Watts:**

1.0 free air all sections

**Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 all sections

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 all sections

**Standard Taper Curve Per Section:**

A all sections

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0