Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-231-8229

## Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-100.0 to 100.0 first temp coefficient

## **Electrical Resistance:**

10.000 kilohms each resistor

# **Resistance Tolerance In Percent:**

-2.000 to 2.000 each resistor

## Ambient Tempurature In Deg Celsius At Full Rated Power:

## 70.0

## Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

## Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0 to 125.0 temp range of first temp coefficient

## **Inclosure Method:**

Encapsulated

## **Terminal Quantity:**

8

## **Terminal Type:**

Pin

## Reliability Indicator:

Not established

## **Terminal Length:**

0.135 inches

## **Body Length:**

0.783 inches

#### **Body Width:**

0.074 inches

#### **Body Height:**

0.187 inches

Schematic Diagram Designator:

Ladder network

#### **Power Dissipation Rating In Watts:**

0.840 total network

#### **End Application:**

Alq176 pod

## Identical Value Resistor Quantity:

7 each resistor

# Unpackaged Unit Weight:

1.5 grams

#### Style Designator:

Single inline

#### **Test Data Document:**

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Film Fixed Resistor Network - Page 2 of 2



**Specification Data:** 

81349-mil-r-83401/8 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A001a0