## NSN 5905-01-232-2752

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-232-2752 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.010 **Terminal Length:** 0.172 inches **Shaft Diameter:** 0.075 inches **Shaft Length:** 0.050 inches **Body Length:** 0.250 inches **Body Width:** 0.165 inches **Body Height:** 0.250 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 3600.0 and 9000.0 **Maximum Starting Torque:** 3.00 inch-ounces **Maximum Running Torque:** 3.00 inch-ounces **Center To Center Distance Between Terminals:** 0.200 inches **End Application:** 4920-01-111-2981 **Terminal Location:** Rear end **Mounting Method:** 

**Terminal** 

**Cubic Measure:** 0.011 cubic inches

## NSN 5905-01-232-2752

No Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
500.000 ohms c and better flooring
Rotary Actuator Travel In Angular Deg:
Between 3600.0 and 9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section
Power Dissipation Rating Per Section In Watts:
0.25 7th secondary quality
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
150.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-39035 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 pin
Specification Data:
81349-mil-r-39035/3 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: