

View Online at <https://aerobasegroup.com/nsn/5905-01-232-5592>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.656 inches

Body Diameter:

0.875 inches

Shaft Diameter:

Between 0.1245 inches and 0.1248 inches

Shaft Length:

1.175 inches

Mounting Bushing Length:

0.375 inches

Body Length:

1.450 inches

Overall Diameter:

1.250 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

360.0

Maximum Starting Torque:

32.00 inch-ounces

Maximum Running Torque:

32.00 inch-ounces

Shaft End Play:

0.005 inches

Shaft Runout:

0.001 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.0015 inches

Shaft Radial Play:

0.003 inches

End Application:

An&apq172 v f

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

4.0 kilohms all sections

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-0.50 to 0.50 all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

70.0 all sections

Power Dissipation Rating Per Section In Watts:

0.5 free air all sections

Function Conformity Per Section:

All sections independent linearity

Resistance Tolerance Per Section In Percent:

-5.0 to 5.0 all sections

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

All sections linear

Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0 to 20.0 all sections

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

125.0 all sections

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Test Data Document:

96214-2496320 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0