

View Online at <https://aerobasegroup.com/nsn/5905-01-232-9746>

**Section Quantity:**

1

**Body Style:**

Rectangular bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

1.872 inches

**Overall Height:**

1.131 inches

**Overall Width:**

0.625 inches

**Shaft Diameter:**

0.125 inches

**Shaft Length:**

0.750 inches

**Mounting Bushing Length:**

0.250 inches

**Body Length:**

1.122 inches

**Body Width:**

0.725 inches

**Body Height:**

0.625 inches

**Shaft Style:**

Round

**Shaft Bearing Type:**

Sleeve

**Switch Type:**

Push-pull

**Switch Voltage Rating In Volts:**

125.0

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

260.0

**Maximum Starting Torque:**

3.00 inch-ounces

**Maximum Running Torque:**

3.00 inch-ounces

**Maximum Stop Torque:**

64.00 inch-ounces

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

0.305 inches

**Switch Operating Position:**

Any position of rotation travel

**Switch Contact Arrangement:**

Single pole, single throw, normally open, both positions maintained

**Fragility Factor:**

Moderately rugged

**End Application:**

Marc

**Screw Thread Diameter:**

0.250 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Right-left adjacent sides

**Mounting Method:**

Standard bushing

**Features Provided:**

Switch

**Cubic Measure:**

1.323 cubic inches

**Electrical Resistance Per Section:**

10.000 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

305.0

**Resistance Temperature Characteristic Range Per Section In Percent:**

+0.0 to 5.0 -55 degrees celsius single section and +0.0 to 3.0 -25 degrees celsius single section and -1.5 to 1.5 0 degrees celsius single section and -2.0 to 2.0 85 degrees celsius single section and -3.0 to 3.0 120 degrees celsius single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

100.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

**Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Switch Current Type And Rating In Amps:**

2.000 ac

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

11 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0