Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-233-1200

Section Quantity:

2

Body Style:

Rectangular w/slide control

Reliability Indicator:

Not established

Overall Length:

21.800 inches

Overall Height:

5.600 inches

Overall Width:

7.250 inches

Mounting Slot Width:

0.250 inches

Body Length:

20.000 inches

Body Width:

7.250 inches

Body Height:

5.600 inches

Actuator Type:

Slider

Longitudinal Actuator Travel:

20.0 inches

Longitudinal Actuator Effective Electrical Stroke Length:

20.000 inches

Fragility Factor:

Moderately rugged

End Application:

An/tsc-99

Mounting Facility Quantity:

4

Terminal Location:

Front-rear

Mounting Method:

Slot

Cubic Measure:

885.080 cubic inches

Electrical Resistance Per Section:

3.75 ohms all sections

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

280.0 all sections

NSN 5905-01-233-1200

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Power Dissipation Rating Per Section In Watts: 2000.0 free air all sections Resistance Tolerance Per Section In Percent: -10.0 to 10.0 all sections Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 all sections Standard Taper Curve Per Section: A all sections Terminal Type And Quantity:

6 binding post

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0