Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-234-3060

#### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

#### **Overall Length:**

3.140 inches

#### First Flat Length:

0.719 inches

#### Flat Height:

0.216 inches

#### Body Diameter:

1.880 inches

#### Shaft Diameter:

0.250 inches

# Shaft Length:

0.875 inches

# Mounting Bushing Length:

0.375 inches

# Body Length:

1.750 inches

#### Shaft Style:

Round, flatted

# Shaft Bearing Type:

Sleeve

#### Actuator Type:

Single shaft

# Effective Electrical Rotation In Deg Angular Rotation:

290.0

#### Maximum Starting Torque:

40.00 inch-ounces

#### Maximum Running Torque:

40.00 inch-ounces

#### Maximum Stop Torque:

240.00 inch-ounces

# Nonturn Device Location:

At 12 oclock

## Nonturn Device Radius:

0.500 inches

## End Application:

Panel cont.



Screw Thread Diameter: 0.375 inches Screw Thread Series Designator: Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 150.0 ohms single section **Rotary Actuator Travel In Angular Deg:** 290.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 340.0 single section **Power Dissipation Rating Per Section In Watts:** 12.5 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section **Standard Taper Curve Per Section:** A single section **Test Data Document:** 81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 3 tab w/screw **Specification Data:** 81349-mil-r-22/4 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** Fiig:

No

A002a0