## NSN 5905-01-234-4698

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-234-4698

Resistance Tolerance In Percent: -1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0  Inclosure Method:
95.000 kilohms  Resistance Tolerance In Percent: -1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0  Inclosure Method:
-1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power:  25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Inclosure Method:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Inclosure Method:
25.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Inclosure Method:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  145.0  Inclosure Method:
145.0 Inclosure Method:
Inclosure Method:
Formal
Encased
Terminal Type:
Wire lead
Reliability Indicator:
Not established
Terminal Length:
Between 1.875 inches and 2.125 inches
Body Diameter:
0.375 inches
Body Length:
Between 0.688 inches and 0.812 inches
Power Dissipation Rating In Watts:
0.333 free air
Style Designator:
Axial terminal each end
Test Data Document:
81349-mil-r-93 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification form
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmenta
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-93/11 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0