

View Online at <https://aerobasegroup.com/nsn/5905-01-234-6345>

Section Quantity:

1

Body Style:

Rectangular bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.938 inches

First Flat Length:

0.625 inches

Flat Height:

0.216 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.969 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.969 inches

Body Width:

0.625 inches

Body Height:

0.725 inches

Shaft Style:

Round, flatted

Shaft Bearing Type:

Sleeve

Switch Type:

Rotary

Switch Voltage Rating In Volts:

125.0

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

260.0

Maximum Starting Torque:

6.00 inch-ounces

Maximum Running Torque:

6.00 inch-ounces

Maximum Stop Torque:

64.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.305 inches

Switch Operating Position:

Start of rotation

Switch Contact Arrangement:

Double pole, single throw, one open, one closed

End Application:

5895-00-069-8758

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Right-left adjacent sides

Mounting Method:

Standard bushing

Features Provided:

Switch

Cubic Measure:

0.439 cubic inches

Electrical Resistance Per Section:

10.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

300.0

Resistance Temperature Characteristic Range Per Section In Percent:

+0.0/+7.0 -55 degrees celsius single section and +0.0/+3.5 -25 degrees celsius single section and +0.0/+2.0 0 degrees celsius single section and -2.5/+2.5 85 degrees celsius single section and +0.0/+5.5 120 degrees celsius single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

1.0 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Switch Current Type And Rating In Amps:

2.000 ac

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

7 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0