## NSN 5905-01-234-9613

Film Fixed Resistor - Page 1 of 1

A001a0



View Online at https://aerobasegroup.com/nsn/5905-01-234-9613

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:  100.0/+100.0  Electrical Resistance:  3.090 kilohms  Resistance Tolerance In Percent:  1.000/+1.000  Ambient Tempurature In Deg Celsius At Full Rated Power:  70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+150.0  Inclosure Method:  Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:
Electrical Resistance: 3.090 kilohms Resistance Tolerance In Percent: 4.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead
Resistance Tolerance In Percent:  1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power:  70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+150.0 nclosure Method: Encapsulated Terminal Type:  Wire lead
Resistance Tolerance In Percent:  1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power:  70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+150.0 nclosure Method: Encapsulated Terminal Type:  Wire lead
Ambient Tempurature In Deg Celsius At Full Rated Power:  70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+150.0 Inclosure Method:  Encapsulated Ferminal Type:  Nire lead
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+150.0 Inclosure Method: Encapsulated Terminal Type: Wire lead
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Fempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+150.0  nclosure Method: Encapsulated  Ferminal Type:  Wire lead
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  150.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+150.0  nclosure Method: Encapsulated  Terminal Type:  Wire lead
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+150.0  nclosure Method: Encapsulated  Terminal Type:  Wire lead
Fempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+150.0  nclosure Method:  Encapsulated  Ferminal Type:  Wire lead
55.0/+150.0  nclosure Method: Encapsulated  Ferminal Type:  Wire lead
nclosure Method: Encapsulated Ferminal Type: Wire lead
Encapsulated  Ferminal Type:  Wire lead
Ferminal Type:  Wire lead
Vire lead
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.001
Terminal Length:
1.250 inches
Body Diameter:
0.066 inches
Body Length:
0.150 inches
Power Dissipation Rating In Watts:
0.125 free air
Test Data Document:
31349-mil-r-39017 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
31349-mil-r-39017/5 government specification
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filig: