

View Online at <https://aerobasegroup.com/nsn/5905-01-236-5254>

Section Quantity:

1

Body Style:

Rectangular w/bushing

Reliability Indicator:

Not established

Shaft Diameter:

Between 5.9 millimeters and 6.0 millimeters

Shaft Length:

Between 39.5 millimeters and 40.5 millimeters

Mounting Bushing Length:

Between 9.7 millimeters and 10.3 millimeters

Body Length:

Between 8.9 millimeters and 9.1 millimeters

Body Width:

Between 16.5 millimeters and 17.5 millimeters

Body Height:

16.5 millimeters

Shaft Style:

Round, slotted

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Nonturn Device Location:

At 9 o'clock

Nonturn Device Radius:

Between 7.1 millimeters and 7.9 millimeters

Fragility Factor:

Moderately rugged

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Features Provided:

Humidity proof

Cubic Measure:

2524.5 cubic centimeters

Electrical Resistance Per Section:

100.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

Between 295.0 and 305.0

Power Dissipation Rating Per Section In Watts:

0.1 free air single section

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 single section

Actuator Travel Control Feature:

Stops

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0