

View Online at <https://aerobasegroup.com/nsn/5905-01-236-5256>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

Between 12.0 millimeters and 12.6 millimeters

**Shaft Diameter:**

Between 5.9 millimeters and 6.0 millimeters

**Shaft Length:**

Between 19.5 millimeters and 20.5 millimeters

**Mounting Bushing Length:**

Between 4.5 millimeters and 5.5 millimeters

**Body Length:**

Between 6.3 millimeters and 7.3 millimeters

**Shaft Style:**

Round, slotted

**Shaft Bearing Type:**

Sleeve

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

Between 295.0 and 305.0

**Fragility Factor:**

Moderately rugged

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Features Provided:**

Humidity proof

**Electrical Resistance Per Section:**

50.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

Between 295.0 and 305.0

**Power Dissipation Rating Per Section In Watts:**

0.05 free air single section

**Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0