

View Online at <https://aerobasegroup.com/nsn/5905-01-236-5256>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

Between 12.0 millimeters and 12.6 millimeters

Shaft Diameter:

Between 5.9 millimeters and 6.0 millimeters

Shaft Length:

Between 19.5 millimeters and 20.5 millimeters

Mounting Bushing Length:

Between 4.5 millimeters and 5.5 millimeters

Body Length:

Between 6.3 millimeters and 7.3 millimeters

Shaft Style:

Round, slotted

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 295.0 and 305.0

Fragility Factor:

Moderately rugged

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Humidity proof

Electrical Resistance Per Section:

50.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

Between 295.0 and 305.0

Power Dissipation Rating Per Section In Watts:

0.05 free air single section

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0