Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-238-6685

## Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-300.0/+300.0

#### **Electrical Resistance:**

5.100 kilohms

#### **Resistance Tolerance In Percent:**

-5.000/+5.000

## Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 70.0

## Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

## Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+125.0

#### **Inclosure Method:**

Encapsulated

#### **Terminal Quantity:**

8

#### - . . . -

Terminal Type:

Pin

#### Reliability Indicator:

Not established

#### **Terminal Length:**

0.135 inches

#### Body Length:

0.783 inches

#### **Body Width:**

0.074 inches

**Body Height:** 

0.187 inches

## Schematic Diagram Designator:

Ladder network

#### Power Dissipation Rating In Watts:

0.840 total network

#### **Terminal Width:**

0.020 inches

#### End Application:

Msgproaxst

## Identical Value Resistor Quantity:

7 each resistor

## Unpackaged Unit Weight:

1.5 grams

## Style Designator:

Single inline

# NSN 5905-01-238-6685

Film Fixed Resistor Network - Page 2 of 2



#### **Test Data Document:**

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-r-83401/8 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A001a0