NSN 5905-01-238-7718

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-238-7718

420.000 ohms Resistance Tolerance In Percent: -1.000 to 1.000 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.186 inches and 1.312 inches Body Length: Between 1.186 inches and 4.594 inches Body Length: Between 2.094 inches and 2.156 inches Body Width: Between 2.094 inches and 2.156 inches Body Height: Between 2.094 inches and 2.156 inches Body Height: Between 2.157 inches and 2.219 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.150 inches and 3.010 inches Power Dissipation Rating In Watts: 75.000 free air Mounting Hole Size: Between 0.178 inches and 0.198 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mill-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and lest conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mill-18546/2 government specification Shelf Life: Na Unit Of Measure: Demilitarization: No Flig:	
Resistance Tolerance in Percent: -1.000 to 1.000 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.188 inches and 1.312 inches Body Length: Between 1.188 inches and 4.594 inches Body Length: Between 2.094 inches and 2.156 inches Body Width: Between 2.094 inches and 2.156 inches Body Height: Between 2.157 inches and 2.219 inches Distance Between Centerlines of Mounting Facilities Parallel To Body Length: Between 2.157 inches and 3.010 inches Power Dissipation Rating in Watts: 75.000 free air Mounting Hole Size: Benween 0.178 inches and 0.198 inches Style Designator: Axial terminal (s) Test Data Document: B1349-mill-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, inclustry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: B1349-mill-18546/2 government specification Specification Short Life: No Unit of Measure: — Demilitarization: No Filig:	Electrical Resistance:
-1.000 to 1.000 Inclosur Method: Encepsulated Erreminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.188 inches and 1.312 inches Body Length: Between 4.406 inches and 4.594 inches Body Length: Between 2.406 inches and 2.156 inches Body Width: Between 2.157 inches and 2.156 inches Body Height: Between 2.157 inches and 2.219 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.157 inches and 3.010 inches Power Dissipation Rating in Watts: 75.000 free air Mounting Hole Size: Between 0.178 inches and 0.198 inches Style Designator: Axial terminal (s) Tost Data Document: Bri349-mil-r18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: Bri349-mil-r18546/2 government specification Shelf Life: No Unit Of Measure: Demilitarization: No Filig:	
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.188 inches and 1.312 inches Body Length: Between 2.084 inches and 4.594 inches Body Width: Between 2.094 inches and 2.156 inches Body Height: Between 2.094 inches and 2.156 inches Body Height: Between 2.095 inches and 2.219 inches Botween 2.090 inches and 3.010 inches Power Dissipation Rating in Watts: 75.000 free air Mounting Hole Size: Between 0.178 inches and 0.198 inches Style Designator: Avail terminal (s) Test Data Document: B1349-mil18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: B1349-mil18546/2 government specification Sheff Life: Na Unit Of Measure: — Demilitarization: No Filig:	
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.188 inches and 1.312 inches Body Length: Between 1.406 inches and 4.594 inches Body Width: Between 2.094 inches and 2.156 inches Body Width: Between 2.094 inches and 2.156 inches Body Height: Between 2.157 inches and 2.219 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.990 inches and 3.010 inches Power Dissipation Rating In Watts: 75.000 free air Mounting Hole Size: Between 0.178 inches and 0.198 inches Style Designator: Avial terminal (s) Test Dat Document: Bit349-mil-1-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: Bit349-mil-1-18546/2 government specification Sheff Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: Between 1.188 inches and 1.312 inches Body Length: Between 4.406 inches and 4.594 inches Body Width: Between 2.094 inches and 2.156 inches Body Height: Between 2.157 inches and 2.219 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.990 inches and 3.010 inches	
Wire lead Reliability Indicator: Not established Terminal Length: Between 1.188 inches and 1.312 inches Body Length: Between 4.406 inches and 4.594 inches Body Width: Between 2.094 inches and 2.156 inches Body Width: Between 2.094 inches and 2.156 inches Body Height: Between 2.157 inches and 2.219 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.990 inches and 3.010 inches Power Dissipation Rating in Watts: 75.000 free air Mounting Hole Size: Between 0.178 inches and 0.198 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-r-18546/2 government specification Shelf Life: N/a Unit Of Measure: Domilitarization: No Fiig:	
Reliability Indicator: Not established Terminal Length: Between 1.188 inches and 1.312 inches Body Length: Between 4.06 inches and 4.594 inches Body Width: Between 2.094 inches and 2.156 inches Body Height: Between 2.094 inches and 2.156 inches Body Height: Between 2.157 inches and 2.219 inches Body Height: Between 2.157 inches and 2.219 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.990 inches and 3.010 inches Power Dissipation Rating In Watts: 75.000 free air Mounting Hole Size: Between 0.178 inches and 0.198 inches Style Designator: Avial terminal (s) Test Data Document: 81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-18546/2 government specification Shelf Life: N/a Unit Of Measure:	Terminal Type:
Not established Terminal Length: Between 1.188 inches and 1.312 inches Body Length: Between 4.406 inches and 4.594 inches Body Width: Between 2.094 inches and 2.156 inches Body Height: Between 2.157 inches and 2.219 inches Body Height: Between 2.157 inches and 2.219 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.990 inches and 3.010 inches Power Dissipation Rating In Watts: 75.000 free air Mounting Hole Size: Between 0.178 inches and 0.198 inches Style Designator: Axial terminal (s) Test Data Document: Ba1349-mil-r-18546/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: B1349-mil-r-18546/2 government specification Sheft Life: N/a Unit Of Measure: Demilitarization: No Flig:	Wire lead
Terminal Length: Between 1.188 inches and 1.312 inches Body Length: Between 4.406 inches and 4.594 inches Body Width: Between 2.094 inches and 2.156 inches Body Height: Between 2.157 inches and 2.156 inches Body Height: Between 2.157 inches and 2.219 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.990 inches and 3.010 inches Power Dissipation Rating In Watts: 75.000 free air Mounting Hole Size: Between 0.178 inches and 0.198 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-18546/2 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Reliability Indicator:
Between 1.188 inches and 1.312 inches Body Length: Between 4.406 inches and 4.594 inches Body Width: Between 2.094 inches and 2.156 inches Body Height: Between 2.157 inches and 2.219 inches Botween 2.157 inches and 2.219 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.990 inches and 3.010 inches Power Dissipation Rating In Watts: 75.000 free air Mounting Hole Size: Between 0.178 inches and 0.198 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-18546/2 government specification Shelf Life: No Unit Of Measure: Demilitarization: No Flig:	Not established
Between 4.406 inches and 4.594 inches Body Width: Between 2.094 inches and 2.156 inches Body Height: Between 2.157 inches and 2.219 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.990 inches and 3.010 inches Power Dissipation Rating In Watts: 75.000 free air Mounting Hole Size: Between 0.178 inches and 0.198 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mili-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mili-18546/2 government specification Shelf Life: N/a Unit Of Measure:	Terminal Length:
Between 4.406 inches and 4.594 inches Body Width: Between 2.094 inches and 2.156 inches Body Height: Between 2.157 inches and 2.219 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.990 inches and 3.010 inches Power Dissipation Rating In Watts: 75.000 free air Mounting Hole Size: Between 0.178 inches and 0.198 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-18546/2 government specification Shelf Life: Na Unit Of Measure: Demilitarization: No Fig:	Between 1.188 inches and 1.312 inches
Body Width: Between 2.094 inches and 2.156 inches Body Height: Between 2.157 inches and 2.219 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.990 inches and 3.010 inches Power Dissipation Rating In Watts: 75.000 free air Mounting Hole Size: Between 0.178 inches and 0.198 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-18546/2 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Body Length:
Between 2.094 inches and 2.156 inches Body Height: Between 2.157 inches and 2.219 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.990 inches and 3.010 inches Power Dissipation Rating In Watts: 75.000 free air Mounting Hole Size: Between 0.178 inches and 0.198 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-18546/2 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 4.406 inches and 4.594 inches
Between 2.157 inches and 2.219 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.990 inches and 3.010 inches Power Dissipation Rating In Watts: 75.000 free air Mounting Hole Size: Between 0.178 inches and 0.198 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-18546/2 government specification Shelf Life: N/a Unit Of Measure:	Body Width:
Between 2.157 inches and 2.219 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.990 inches and 3.010 inches Power Dissipation Rating In Watts: 75.000 free air Mounting Hole Size: Between 0.178 inches and 0.198 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-18546/2 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 2.094 inches and 2.156 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 2.990 inches and 3.010 inches Power Dissipation Rating In Watts: 75.000 free air Mounting Hole Size: Between 0.178 inches and 0.198 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-18546/2 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Height:
Between 2.990 inches and 3.010 inches Power Dissipation Rating In Watts: 75.000 free air Mounting Hole Size: Between 0.178 inches and 0.198 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-18546/2 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 2.157 inches and 2.219 inches
Power Dissipation Rating In Watts: 75.000 free air Mounting Hole Size: Between 0.178 inches and 0.198 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-18546/2 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
Mounting Hole Size: Between 0.178 inches and 0.198 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-18546/2 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 2.990 inches and 3.010 inches
Mounting Hole Size: Between 0.178 inches and 0.198 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-18546/2 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Power Dissipation Rating In Watts:
Between 0.178 inches and 0.198 inches Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-18546/2 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	75.000 free air
Style Designator: Axial terminal (s) Test Data Document: 81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-18546/2 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Mounting Hole Size:
Axial terminal (s) Test Data Document: 81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-18546/2 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Between 0.178 inches and 0.198 inches
Test Data Document: 81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-18546/2 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-18546/2 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal (s)
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-18546/2 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-18546/2 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-r-18546 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Specification Data: 81349-mil-r-18546/2 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
81349-mil-r-18546/2 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Specification Data:
N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-r-18546/2 government specification
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
	Fiig: