

View Online at <https://aerobasegroup.com/nsn/5905-01-238-8548>

**Section Quantity:**

1

**Body Style:**

Rectangular

**Reliability Indicator:**

Not established

**Body Length:**

0.750 inches

**Body Width:**

0.250 inches

**Body Height:**

0.190 inches

**Shaft Bearing Type:**

Sleeve

**Actuator Type:**

Flush drive with slot-hole

**Effective Electrical Rotation In Deg Angular Rotation:**

7200.0

**Maximum Starting Torque:**

5.00 inch-ounces

**Maximum Running Torque:**

5.00 inch-ounces

**Terminal Location:**

Lower adjacent side two rows

**Mounting Method:**

Terminal

**Cubic Measure:**

0.035 cubic inches

**Electrical Resistance Per Section:**

500.000 percent, rated amperes c and better flooring

**Rotary Actuator Travel In Angular Deg:**

7200.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-100.0/+100.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.0 7th secondary quality

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Clutch

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

70.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0