NSN 5905-01-238-8744

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-238-8744 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.1243 inches **Shaft Length:** 0.380 inches **Mounting Bushing Length:** 0.310 inches **Body Length:** 1.100 inches **Mounting Lip Diameter:** 0.8750 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Fragility Factor:** Moderately rugged **Screw Thread Diameter:** Between 0.280 inches and 0.281 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Standard bushing **Features Provided:** Humidity proof

Electrical Resistance Per Section:

100.000 megohms single section

Power Dissipation Rating Per Section In Watts:

0.7 free air single section

NSN 5905-01-238-8744

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
5 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0