Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-238-9039

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.345 inches

Body Diameter:

0.875 inches

Shaft Diameter:

0.2497 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

0.405 inches

Body Length:

0.345 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

340.0

Maximum Starting Torque:

0.70 inch-ounces

Maximum Running Torque:

0.50 inch-ounces

Nonturn Device Location:

At 12 oclock

Nonturn Device Radius:

0.312 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.005 inches

Shaft Radial Play:

0.003 inches

End Application:

Set vi config



Screw T	hread Diameter:
0.375 inc	hes
Screw T	hread Series Designator:
Unef	
Screw T	hready Qty Per Inch (tpi):
32.0	
Termina	Location:
Rear end	
Mountin	g Method:
Standard	bushing
Electrica	I Resistance Per Section:
220.000	percent, rated amperes c and better flooring
Rotary A	ctuator Travel In Angular Deg:
360.0	
Functior	Conformity Tolerance Per Section:
-1.00/+1.	00 single section
Ambient	Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 sir	gle section
Tempura	ature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+′	100.0 single section
Power D	issipation Rating Per Section In Watts:
3.5 7th s	econdary quality
Functior	Conformity Per Section:
Single se	ction independent linearity
Resistar	ce Tolerance Per Section In Percent:
·5.0/+5.0	single section
Actuato	Travel Control Feature:
Continuo	us motion
Functior	Characteristic Per Section:
7 oclock	all primaries
Ambient	Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 sing	le section
Termina	Type And Quantity:
3 turret	
Shelf Lif	e:
N/a	
Unit Of I	Neasure:
Demilita	rization:
No	
Fiig:	
3-	