NSN 5905-01-239-5051

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-239-5051

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:				
-30.0/+30.0				
Electrical Resistance:				
383.000 ohms				
Resistance Tolerance In Percent:				
-1.000/+1.000				
Ambient Tempurature In Deg Celsius At Full Rated Power:				
25.0				
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:				
275.0				
Tempurature Range Of Tempurature Coefficient In Deg Celsius:				
-55.0/+275.0				
Inclosure Method:				
Encased				
Terminal Type:				
Tab, solder lug				
Reliability Indicator:				
Established				
Reliability Failure Rate Level In Percent:				
0.010				
Terminal Length:				
0.438 inches				
Body Length:				
1.938 inches				
Body Width:				
0.594 inches				
Body Height:				
0.625 inches				
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:				
1.562 inches				
Power Dissipation Rating In Watts:				
10.000 free air				
Terminal Width:				
0.140 inches				
End Application:				
F16aircombfit				
Mounting Hole Size:				
0.125 inches				
Cubic Measure (non-core):				
0.719 cubic inches				
Unpackaged Unit Weight:				

35.0 grams

NSN 5905-01-239-5051

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



~ .			
Stvie	e Des	sıan	ator:

Axial terminal (s)

Test Data Document:

81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-r-39009/2 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0