

View Online at <https://aerobasegroup.com/nsn/5905-01-240-2224>

Section Quantity:

2

Body Style:

Rectangular w/bushing

Reliability Indicator:

Not established

Shaft Length:

30.0 millimeters

Shaft Style:

Round, stepped

Shaft Bearing Type:

Sleeve

Switch Type:

Push-pull

Actuator Type:

Single shaft

Nonturn Device Location:

At 9 oclock

Switch Operating Position:

Any position of rotation travel

Switch Contact Arrangement:

Single pole, single throw, normally closed

Fragility Factor:

Moderately rugged

Undercut Length:

3.2 millimeters

Screw Thread Diameter:

0.750 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Humidity proof and switch

Electrical Resistance Per Section:

100.0 percent, rated amperes c and better industrial clears

Actuator Travel Control Feature:

Stops

Standard Taper Curve Per Section:

A all sections

Special Features:

W/rotary spstno switch which is turned on by full counterclockwise rotation

Terminal Type And Quantity:

3 pin and 8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0