

View Online at <https://aerobasegroup.com/nsn/5905-01-240-4008>

**Section Quantity:**

1

**Body Style:**

Rectangular

**Reliability Indicator:**

Not established

**Terminal Length:**

3.75 millimeters

**Body Length:**

5.9 millimeters

**Body Width:**

6.9 millimeters

**Body Height:**

8.0 millimeters

**Actuator Type:**

Flush drive with slot-hole

**Effective Electrical Rotation In Deg Angular Rotation:**

200.0

**Maximum Starting Torque:**

200.00 centimeter-grams

**Maximum Running Torque:**

200.00 centimeter-grams

**Center To Center Distance Between Terminals:**

5.0 millimeters

**Fragility Factor:**

Moderately delicate

**End Application:**

6625-01-146-5801

**Terminal Location:**

Lower adjacent side two rows

**Mounting Method:**

Terminal

**Center To Center Distance Between Terminal Rows:**

2.5 millimeters

**Cubic Measure:**

276.0 cubic centimeters

**Electrical Resistance Per Section:**

10.000 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

200.0

**Center To Center Distance Between Center Terminal And Outside Terminal:**

2.5 millimeters

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

70.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-200.0/+200.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.33 free air single section

**Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

60.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0