NSN 5905-01-240-4010

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-240-4010 **Section Quantity: Body Style:** Rectangular **Reliability Indicator:** Not established **Terminal Length:** 0.157 inches **Body Length:** 0.149 inches **Body Width:** 0.400 inches **Body Height:** 0.400 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 240.0 **Maximum Starting Torque:** 2.00 inch-ounces **Maximum Running Torque:** 2.00 inch-ounces **Maximum Stop Torque:** 3.00 inch-ounces **Center To Center Distance Between Terminals:** 0.200 inches **Fragility Factor:** Moderately delicate **Terminal Location:** Lower adjacent side two rows **Mounting Method: Terminal Center To Center Distance Between Terminal Rows:** 0.100 inches **Cubic Measure:** 0.024 cubic inches **Electrical Resistance Per Section:** 100.000 kilohms single section

240.0

Rotary Actuator Travel In Angular Deg:

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

NSN 5905-01-240-4010

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
70.0 single section
Power Dissipation Rating Per Section In Watts:
0.1 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No