NSN 5905-01-240-6401

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-240-6401 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established First Flat Length: 0.500 inches Flat Height: Between 0.097 inches and 0.107 inches **Body Diameter:** 0.288 inches **Shaft Diameter:** Between 0.271 inches and 0.291 inches **Shaft Length:** 1.000 inches **Mounting Bushing Length:** 0.906 inches **Body Length:** 1.076 inches **Shaft Style:** Round, flatted **Actuator Type:** Single shaft **Maximum Starting Torque:** 8.00 inch-ounces **Maximum Running Torque:** 8.00 inch-ounces **Terminal Location:** Longitudinally positioned on the circumference **Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 10.0 kilohms single section **Power Dissipation Rating Per Section In Watts:** 1.5 free air single section **Resistance Tolerance Per Section In Percent:** -1.0/+1.0 single section Shelf Life: N/a

Unit Of Measure:

NSN 5905-01-240-6401

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Demi			

No

Fiig:

A002a0