Nonprecision Wire Wound Variable Resistor - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5905-01-240-6401

Section Quantity:

1

Body Style: Cylindrical bushing mounted **Reliability Indicator:** Not established First Flat Length: 0.500 inches Flat Height: Between 0.097 inches and 0.107 inches **Body Diameter:** 0.288 inches Shaft Diameter: Between 0.271 inches and 0.291 inches Shaft Length: 1.000 inches Mounting Bushing Length: 0.906 inches **Body Length:** 1.076 inches Shaft Style: Round, flatted Actuator Type: Single shaft **Maximum Starting Torque:** 8.00 inch-ounces

Maximum Running Torque:

8.00 inch-ounces

Terminal Location:

Longitudinally positioned on the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

10.0 kilohms single section

Power Dissipation Rating Per Section In Watts:

1.5 free air single section

Resistance Tolerance Per Section In Percent:

-1.0/+1.0 single section

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5905-01-240-6401

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0