

View Online at <https://aerobasegroup.com/nsn/5905-01-240-9174>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.250 inches

Body Diameter:

0.875 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.875 inches

Mounting Bushing Length:

0.313 inches

Body Length:

1.500 inches

Overall Diameter:

1.250 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

0.70 inch-ounces

Maximum Running Torque:

0.60 inch-ounces

Maximum Stop Torque:

48.00 inch-ounces

Nonturn Device Location:

At 12 oclock

Nonturn Device Radius:

0.302 inches

Shaft End Play:

0.00500 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.00100 inches

Shaft Radial Play:

0.002 inches

Mechanical Backlash In Deg Angular Rotation:

1.5

End Application:

Control drawe

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Cubic Measure:

2.761 cubic inches

Electrical Resistance Per Section:

5.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

3600.0

Function Conformity Tolerance Per Section:

-1.00/+1.00 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Resistance Tolerance Per Section In Percent:

-1.0/+1.0 single section

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Test Data Document:

81349-mil-r-12934 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 tab, solder lug

Specification Data:

81349-mil-r-12934/31 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0