

View Online at <https://aerobasegroup.com/nsn/5905-01-241-5910>

**Section Quantity:**

1

**Body Style:**

Cylindrical servo mounted

**Reliability Indicator:**

Not established

**Pilot Diameter:**

0.7500 inches

**Pilot Length:**

0.0620 inches

**Undercut Diameter:**

0.781 inches

**Undercut Width:**

0.0570 inches

**Body Diameter:**

0.906 centimeters

**Shaft Diameter:**

0.125 inches

**Shaft Length:**

1.000 inches

**Body Length:**

1.625 inches

**Mounting Lip Diameter:**

0.8750 inches

**Mounting Lip Depth:**

0.0620 inches

**Shaft Style:**

Round

**Shaft Bearing Type:**

Bearing

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

3600.0

**Maximum Starting Torque:**

0.70 inch-ounces

**Maximum Running Torque:**

0.60 inch-ounces

**Maximum Stop Torque:**

48.00 inch-ounces

**Fragility Factor:**

Moderately rugged

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Clamp ring

**Features Provided:**

Humidity proof

**Cubic Measure:**

1.050 cubic inches

**Electrical Resistance Per Section:**

5.000 percent, rated amperes c and better flooring

**Rotary Actuator Travel In Angular Deg:**

3600.0

**Function Conformity Tolerance Per Section:**

-0.10/+0.10 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-30.0/+30.0 single section

**Power Dissipation Rating Per Section In Watts:**

2.0 7th secondary quality

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-1.0/+1.0 single section

**Actuator Travel Control Feature:**

Stops

**Function Characteristic Per Section:**

7 oclock all primaries

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

85.0 single section

**Test Data Document:**

81349-mil-r-12934 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 tab, solder lug

**Specification Data:**

81349-mil-r-12934/6 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

1-000-0