

View Online at <https://aerobasegroup.com/nsn/5905-01-241-9045>

Electrical Resistance:

10.0 kilohms and 1.0 kilohms and 24.9 ohms and 51.1 kilohms and 511.0 ohms and 5.11 kilohms and 2.15 kilohms

Resistance Tolerance In Percent:

-1.0/+1.0 and -1.0/+1.0 and -1.0/+1.0 and -1.0/+1.0 and -1.0/+1.0 and -1.0/+1.0 and -1.0/+1.0

Terminal Quantity:

4 and 2 and 4 and 4 and 6 and 4 and 2

Terminal Type:

Wire lead and wire lead and wire lead and wire lead and wire lead and wire lead and wire lead

Resistor Power Dissipation Rating In Watts:

0.25 and 0.25 and 1.0 and 0.25 and 0.25 and 0.25 and 0.25

Mounting Method:

Solder

End Application:

4920-01-121-6670nt

Component Quantity:

2 and 1 and 2 and 2 and 3 and 2 and 1

Mounting Configuration:

Spaces even for 24 resistors, 1 through 13 used

Component Controlling Agency:

Honeywell; honeywell; honeywell; honeywell; honeywell; honeywell; honeywell

Component Name:

Fixed film resistor; fixed film resistor; fixed wire wound resistor; fixed film resistor; fixed film resistor; fixed film resistor; fixed film resistor

Component Identifying Number:

Rlr07c1002fr part no. And rlr07c1001fr part no. And rwr81s24r9fr part no. And rlr07c5112fr part no. And rlr07c5110fr part no. And rlr07c5111fr part no. And rlr07c2151fr part no.

Assembly Construction Method:

Mounted on terminal board

Component Relationship:

Not matched

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T172-f