NSN 5905-01-242-5632

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-242-5632 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.125 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.1248 inches **Shaft Length:** 1.175 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.950 inches **Overall Diameter:** 0.875 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 335.0 **Maximum Starting Torque:** 32.00 inch-ounces **Maximum Running Torque:**

5.60 inch-ounces **Shaft End Play:** 0.00500 inches **Shaft Runout:** 0.001 inches **Lateral Runout:** 0.002 inches **Pilot Diameter Runout:** 0.00150 inches **Shaft Radial Play:** 0.003 inches

NSN 5905-01-242-5632

Precision Wire Wound Variable Resistor - Page 2 of 3



Fragility Factor:
Moderately rugged
End Application:
An and apq172 v f
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Standard bushing
Cubic Measure:
1.278 cubic inches
Electrical Resistance Per Section:
10.000 percent, rated amperes c and better flooring
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
165.0 single section
Rotary Actuator Travel In Angular Deg:
335.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 7th secondary quality
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Function Characteristic Per Section: 7 oclock all primaries
7 oclock all primaries
7 oclock all primaries Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

Gold

Precious Material:

NSN 5905-01-242-5632

Precision Wire Wound Variable Resistor - Page 3 of 3



Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0