NSN 5905-01-242-6967

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-242-6967

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
|---|
| -5.0/+5.0 first temp coefficient |
| Electrical Resistance: |
| 43.240 kilohms |
| Resistance Tolerance In Percent: |
| -0.100/+0.100 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 125.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 175.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0/+125.0 temp range of first temp coefficient |
| Inclosure Method: |
| Encapsulated Encapsulated |
| Terminal Type: |
| Wire lead |
| Reliability Indicator: |
| Established |
| Reliability Failure Rate Level In Percent: |
| 1.000 |
| Terminal Length: |
| 0.875 inches |
| Body Length: |
| 0.295 inches |
| Body Width: |
| 0.100 inches |
| Body Height: |
| 0.320 inches |
| Power Dissipation Rating In Watts: |
| 0.300 free air |
| End Application: |
| Mk-48 torpedo |
| Cubic Measure (non-core): |
| 0.010 cubic inches |
| Special Features: |
| Burn-in required |
| Unpackaged Unit Weight: |
| 1.0 grams |
| Style Designator: |
| Terminals one edge |
| Test Data Document: |

53711-5529383 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

NSN 5905-01-242-6967

Film Fixed Resistor - Page 2 of 2



| C | ha | Ιf | 1 | ife | |
|---|-----|----|---|-------|--|
| • | ııe | | _ | .II C | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0