## NSN 5905-01-242-7411

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-242-7411

| The second of th |
|--|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:  |
| -600.0/+600.0  |
| Electrical Resistance:   |
| 0.220 ohms   |
| Resistance Tolerance In Percent:   |
| -5.000/+5.000  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 70.0   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| 160.0  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:   |
| -55.0/+160.0   |
| Inclosure Method:  |
| Encapsulated   |
| Terminal Type:   |
| Wire lead  |
| Reliability Indicator:   |
| Not established  |
| Terminal Length:   |
| 1.500 inches   |
| Body Diameter:   |
| 0.225 inches   |
| Body Length:   |
| 0.562 inches   |
| Power Dissipation Rating In Watts:   |
| 2.000 free air   |
| End Application:   |
| Pwr.Producer   |
| Cubic Measure (non-core):  |
| 0.022 cubic inches   |
| Special Features:  |
| Temp coef not to exceed plus 800 ppm   |
| Style Designator:  |
| Axial terminal each end  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |

A001a0