

View Online at https://aerobasegroup.com/nsn/5905-01-242-8709

# Section Quantity:

1

Body Style:

Rectangular

# Reliability Indicator:

Not established

# **Overall Length:**

0.285 inches

# Terminal Length:

0.200 inches

#### **Overall Height:**

0.250 inches

#### **Overall Width:**

0.375 inches

#### Shaft Diameter:

0.070 inches

# Shaft Length:

0.035 inches

# Body Length:

0.250 inches

# Body Width:

0.175 inches

# Body Height:

0.250 inches

### Shaft Style:

Round, slotted

### Actuator Type:

Single shaft

### Maximum Starting Torque:

3.00 inch-ounces

### Maximum Running Torque:

3.00 inch-ounces

### Center To Center Distance Between Terminals:

0.200 inches

#### **Fragility Factor:**

Moderately rugged

# **End Application:**

5840-01-084-2444

# **Terminal Location:**

Left adjacent side two rows

# Mounting Method:

Terminal



**Center To Center Distance Between Terminal Rows:** 0.100 inches **Cubic Measure:** 0.027 cubic inches **Electrical Resistance Per Section:** 20.000 ohms c and better flooring **Rotary Actuator Travel In Angular Deg:** 7200.0 Center To Center Distance Between Center Terminal And Outside Terminal: 0.100 inches Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -10.0/+10.0 single section **Power Dissipation Rating Per Section In Watts:** 0.25 7th secondary quality **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 85.0 single section Standard Taper Curve Per Section: A single section **Terminal Type And Quantity:** 3 pin Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig:

A002a0