## NSN 5905-01-242-9369

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-242-9369 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Body Diameter:** Between 0.769 inches and 0.801 inches **Body Length:** Between 0.640 inches and 0.672 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 240.0 **Maximum Starting Torque:** 8.00 inch-ounces **Maximum Running Torque:** 8.00 inch-ounces **Terminal Location:** Rear end **Mounting Method:** Tab **Features Provided:** Grounded contact arm **Electrical Resistance Per Section:** 1.8 kilohms single section **Rotary Actuator Travel In Angular Deg:** 240.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Power Dissipation Rating Per Section In Watts:** 1.5 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 55.0 single section **Standard Taper Curve Per Section:** A single section

**Terminal Type And Quantity:** 2 tab, solder lug

## NSN 5905-01-242-9369

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Shelf Life:		
N/a		
Unit Of Measure:		
_		

Demilitarization:

No

Fiig:

A002a0