## NSN 5905-01-243-6137

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-243-6137 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.094 inches **Shaft Diameter:** Between 0.248 inches and 0.251 inches **Mounting Bushing Length:** Between 0.344 inches and 0.390 inches **Body Length:** Between 0.719 inches and 0.875 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Mounting Facility Quantity: Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 750.000 ohms single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5905-01-243-6137

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0