

View Online at <https://aerobasegroup.com/nsn/5905-01-243-9761>

Section Quantity:

2

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.7495 inches

Pilot Length:

0.0620 inches

Overall Length:

2.065 inches

Undercut Diameter:

0.781 inches

Undercut Width:

0.0570 inches

Body Diameter:

0.900 inches

Shaft Diameter:

0.1248 inches

Shaft Length:

0.625 inches

Body Length:

1.440 inches

Overall Diameter:

1.210 inches

Mounting Lip Diameter:

0.9000 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round

Shaft Bearing Type:

Ball

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

360.0

Maximum Starting Torque:

0.80 inch-ounces

Maximum Running Torque:

0.80 inch-ounces

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Clamp ring

Electrical Resistance Per Section:

5.0 kilohms all sections

Rotary Actuator Travel In Angular Deg:

360.0

Function Conformity Tolerance Per Section:

-1.00/+1.00 all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 all sections

Power Dissipation Rating Per Section In Watts:

1.0 free air all sections

Function Conformity Per Section:

All sections independent linearity

Fixed Tap Quantity Per Section:

1 all sections

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Actuator Travel Control Feature:

Continuous motion

Function Characteristic Per Section:

All sections linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 all sections

Terminal Type And Quantity:

8 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0