NSN 5905-01-244-0318

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-244-0318

| Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Inclosure Mothod: Encapsulated Terminal Type: Wire laad Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 Incles Body Diameter: Between 0.281 inches and 0.343 inches Body Length: Between 0.813 inches and 0.937 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end 18439-mili-73007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average*, "", etc.). Specification Data: 81349-mili-730007 fig overnment specification Shelf Life: Na Unit of Measure: | Electrical Resistance: |
|--|--|
| -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Inclosure Method: Encapsulated Terminal Type: Wife lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: Between 0.281 inches and 0.343 inches Body Length: Between 0.813 inches and 0.393 inches Power Dissipation Rating In Watts: 7.000 free air Style Dasignator: Axial terminal each end Test Data Document: 81349-milr-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-milr-39007/10 government specification Specification Data: 81349- | 64.900 ohms |
| Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: Between 0.281 inches and 0.343 inches Body Length: Between 0.813 inches and 0.343 inches Body Length: Eetween 0.811 inches and 0.337 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mili-739007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mili-739007 tog overnment specification Sheft Life: Na Unit Of Measure: | Resistance Tolerance In Percent: |
| 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Icolosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: Between 0.281 inches and 0.343 inches Body Diameter: Between 0.813 inches and 0.937 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Tests Data Document: 814349-milr-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-milr-39007/10 government specification Sheft Life: N/a Unit Of Measure: | -1.000/+1.000 |
| Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Torminal Length: 1.500 inches Body Diameter: Between 0.281 inches and 0.343 inches Body Diameter: Between 0.813 inches and 0.343 inches Rower Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-r-39007/10 government specification Shelf Life: N/a Unit of Measure: | Ambient Tempurature In Deg Celsius At Full Rated Power: |
| Inclosure Method: Encapsulated Terminal Type: Write lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: Between 0.281 inches and 0.343 inches Body Diameter: Between 0.281 inches and 0.343 inches Roby Length: Between 0.813 inches and 0.937 inches Power Dissipation Rating in Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/10 government specification Shelf Life: N/a Unit Of Measure: | 25.0 |
| Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: Between 0.813 inches and 0.343 inches Body Length: Between 0.813 inches and 0.337 inches Power Dissipation Rating in Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type builletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-3900710 government specification Shelf Life: Na Unit Of Measure: | Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| Encapsulated Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: Between 0.281 inches and 0.343 inches Body Length: Between 0.813 inches and 0.343 inches Body Length: 8 Detween 0.813 inches and 0.937 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-milr-39007/10 government specification Shelf Life: N/a Unit Of Measure: | 275.0 |
| Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: Between 0.281 inches and 0.343 inches Body Length: Between 0.813 inches and 0.343 inches Reliability Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document: B1349-mill-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: B1349-mill-r-39007/10 government specification Shelf Life: N/a Unit Of Measure: | Inclosure Method: |
| Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: Between 0.281 inches and 0.343 inches Body Length: Between 0.813 inches and 0.343 inches Body Length: Between 0.813 inches and 0.937 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-milr-39007/10 government specification Shelf Life: V/a Unit Of Measure: | Encapsulated |
| Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: Between 0.281 inches and 0.343 inches Body Length: Between 0.813 inches and 0.937 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mill-7.39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mill-7.39007/10 government specification Sheft Life: N/a Unit Of Measure: | Terminal Type: |
| Established Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: Between 0.281 inches and 0.343 inches Body Length: Between 0.813 inches and 0.937 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/10 government specification Na Unit Of Measure: Demilitarization: No Fig: | Wire lead |
| Reliability Failure Rate Level In Percent: 0.001 Terminal Length: 1.500 inches Body Diameter: Between 0.281 inches and 0.343 inches Body Length: Between 0.813 inches and 0.937 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/10 government specification N/a Unit Of Measure: | Reliability Indicator: |
| Terminal Length: 1.500 inches Body Diameter: Between 0.281 inches and 0.343 inches Body Length: Between 0.813 inches and 0.937 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/10 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Established |
| Terminal Length: 1.500 inches Body Diameter: Between 0.281 inches and 0.343 inches Body Length: Between 0.813 inches and 0.937 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/10 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Reliability Failure Rate Level In Percent: |
| 1.500 inches Body Diameter: Between 0.281 inches and 0.343 inches Body Length: Between 0.813 inches and 0.937 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/10 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | 0.001 |
| Between 0.281 inches and 0.343 inches Body Length: Between 0.813 inches and 0.937 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/10 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Figs: | Terminal Length: |
| Between 0.281 inches and 0.343 inches Body Length: Between 0.813 inches and 0.937 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/10 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Figs: | 1.500 inches |
| Between 0.813 inches and 0.937 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/10 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Body Diameter: |
| Between 0.813 inches and 0.937 inches Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/10 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Between 0.281 inches and 0.343 inches |
| Power Dissipation Rating In Watts: 7.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/10 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Body Length: |
| 7.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/10 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Between 0.813 inches and 0.937 inches |
| Style Designator: Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/10 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Power Dissipation Rating In Watts: |
| Axial terminal each end Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/10 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | 7.000 free air |
| Test Data Document: 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/10 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Style Designator: |
| 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/10 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Axial terminal each end |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/10 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Test Data Document: |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-39007/10 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | 81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| Specification Data: 81349-mil-r-39007/10 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| 81349-mil-r-39007/10 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Specification Data: |
| N/a Unit Of Measure: Demilitarization: No Fiig: | 81349-mil-r-39007/10 government specification |
| Unit Of Measure: Demilitarization: No Fiig: | Shelf Life: |
| Demilitarization: No Fiig: | N/a |
| No Fiig: | Unit Of Measure: |
| No Fiig: | _ |
| Fiig: | Demilitarization: |
| | No |
| A001a0 | Fiig: |
| | A001a0 |